

PRODUCT

MEDIAONE 4A

DESCRIPTION

ACTIVE STUDIO MONITORS

SERIES

MEDIAONE

CATEGORY

MONITORS**GENERAL DESCRIPTION**

The MediaOne 4a monitors produce a powerful, full-range sound thanks to the internal 40 watt amplifier, extended range copolymer woofer and 25mm silk dome tweeter. Completely versatile, these monitors are ideal for a digital recording studio, video production suite or enhancing audio at any computer workstation.

The 4-inch custom designed woofer of the MediaOne 4a delivers tight and controlled low frequency response, while the silk dome high frequency driver is set in a custom waveguide that produces an accurate and natural high frequency response. The result is solid bass response and extended highs, all in an amazingly compact cabinet.

An internal 2 x 20 watt high performance, low distortion, stereo power amplifier drives both sides, and the right side cabinet also houses a convenient, front control panel with volume control and headphone output. There is also a 3.5mm auxiliary input for connecting a second signal source like an MP3 player, keyboard, sound card or any other stereo line level signal.

The rear panel has RCA inputs, terminals for connecting the passive monitor, a power switch and AC power. The precision-tuned enclosures, which incorporate rear venting for extended low frequency response, are finished in an attractive black satin vinyl covering, assuring these monitors look as good as they sound.

FEATURES

- > Precision tuned, rear-vented enclosure
- > 4-inch copolymer woofer
- > 25mm silk dome high frequency driver
- > 2 x 20 watts of Class A/B internal power
- > Front panel level control, headphones and 1/8-inch / 3.5mm stereo input jack
- > Convenient rear panel RCA inputs
- > Attractively finished in black satin vinyl covering
- > AV shielded for multimedia applications
- > Passive crossovers utilizing a multi-pole design for linear response from bottom to top
- > 2 meter, 18-gauge speaker cable included

PRODUCT SPECIFICATION SHEET

MEDIAONE 4a

SERIES
MEDIAONE

DESCRIPTION
ACTIVE STUDIO MONITORS

CATEGORY
MONITORS

ARCHITECT'S & ENGINEER'S SPECIFICATIONS

The MediaOne active studio monitors from Samson shall come in 3 sizes. The 3a, 4a, and 5a. The MediaOne 3a shall have a stereo 15 watt amplifier. The 4a and 5a shall have stereo 20 watt amplifiers. All three models shall have front a front panel power LED indicators, volume control, aux input, and headphone output on 1/8th inch jack. All three models shall use a 25mm silk dome tweeter. The 3a, 4a, and 5a shall use a custom designed copolymer 3-inch, 4-inch and 5-inch woofers respectively. All three models shall use multi-pole passive crossover designs. The rear panels shall have power on/off switches, RCA inputs, and power AC input. All three models shall be AV shielded for multimedia use. All three models shall be covered in a black satin vinyl finish. 18 gauge speaker wires shall be included.

MEDIAONE 4A SPECIFICATIONS

Frequency Response	54 Hz - 23 kHz, -10 dB
Amplifier Power Rating	2 x 20 watts RMS
Crossover Frequency	3.3 kHz: HPF, 6 dB/oct, LPF 12 dB/oct
Inputs	Unbalanced: -10dBv line level Connectors: RCA (rear panel), 3.5mm (front panel)
Enclosure	Construction: MDF (Medium Density Fiberboard)
Finish	Black textured vinyl covering
Dimensions	Active: 6.625" (w) x 9" (d) x 9.125" (h) 168mm x 229mm x 232mm Passive: 6.625" (w) x 7.625" (d) x 9.125" (h) 168mm x 194mm x 232mm
Weight	Active: 9.5 lbs • 4.3 kg Passive: 6.5 lbs • 3 kg

